

VÁLVULAS DE MARIPOSA / BUTTERFLY VALVES

VÁLVULA DE MARIPOSA WAFER TOTAL INOX CON ASIENTO EPDM. PN16 PALANCA WAFFER TYPE BUTTERFLY VALVE FULL S.STEEL WITH EPDM SEAT. PN16 LEVER



TECFLOW®

TF-BFV-W-SS



UTILIZACIÓN / APPLICATION :

Agua fría y caliente, agua de mar, alcoholes, hidróxido de sosa, agua demineralizada, mercurio, alcalinos
Cold and hot wate, sea water, alcohol, hydroxyd of soda, demineralized water, mercury, alcalins.

CARACTERÍSTICAS GENERALES / GENERAL CHARACTERISTICS :

Válvulas Wafer de eje centrado / Full crossing stem wafer type design.

Rango desde DN32 hasta DN300 / Range from ND32 up to ND300 .

Cierre bidireccional / Bidirectional close.

Estanqueidad 100% / 100% tightness.

Palanca de 9 posiciones / Handle with locking device.

Pletina montaje ISO 5211 / ISO 5211 mounting pad.

NORMATIVAS / STANDARDS :

Fabricación / Manufacture according to : ISO 9001: 2015.

Diseño / Designing according to : ISO 10631 & EN 593.

Directiva CE / Directive 2014/68/EU: CE No.0038 Risk Category III Module H.

Distancia entre caras / Face to Face : EN 558-1 Serie 20.

Montaje entre bridas / Mounting between flanges EN1092-1 PN10/16 - ANSI150.

Pruebas de estanqueidad / Tightness Test according to : EN 12266-1 Rate A.

ATEX / ATEX Group II Category 2 G/2D Zone 1 & 21 Zone 2 & 22 (Optional marking).

CONDICIONES DE SERVICIO / WORKING CONDITIONS:


Máxima presión de trabajo / Maximum Working Pressure : 16 bar.

Temperatura máxima de trabajo / Maximum Working Temperature : - 20 °C / + 110 °C.



MATERIALES / CONSTRUCTION :


No.	Pieza Part	Material Material
1	Cuerpo Body	ASTMA351 CF8M
2	Disco Disc	ASTMA351 CF8M
3	Asiento Seat	EPDM
4	Eje Shaft	A.Inox AISI316 SS 316
5	Junta O-Ring	NBR
6	Anillo Ring	A.Inox AISI316 SS 316
7	Circlip Circlip	A.Inox AISI316 SS 316
8	Placa Plate	ASTMA351 CF8M
9	Tornillo Placa Plate Screw	A4
10	Arandela Washer,	A.Inox AISI316 SS 316



DIMENSIONES / DIMENSIONS :


DN ND	A	B	ØDe	E	ØF	H4	C	ØK	ISO	NxØZ	ØK1	ISO 1	NxØZ1	Par Nm Torque	NxØZ1	Peso Weight
32/40	206	140	82	33	9,5	14	8	70	F07	4 x 9	50	F05	4 x 7	9	4 x 7	2,48
50	228	156	102	43	9,5	14	8	70	F07	4 x 9	50	F05	4 x 7	11	4 x 7	3,66
65	248	161	119	46	12	16	9	70	F07	4 x 9	50	F05	4 x 7	20	4 x 7	4,4
80	265	169	135	46	14	16	11	70	F07	4 x 9	50	F05	4 x 7	29	4 x 7	4,6
100	298	187	155	52	14	20	11	70	F07	4 x 9	50	F05	4 x 7	47	4 x 7	6
125	331	206	185	56	17	20	14	70	F07	4 x 9				82		7,6
150	349	215	208	56	17	20	14	70	F07	4 x 9				130		9,2
200	430	255	270	60	21	24	17	70	F07	4 x 9				210		14,7

Par en Nm CON coeficiente de seguridad del 30% para 16 Bar / Torque Values in Nm WITH 30% safety coefficient at 16 Bar.



(*) : Only from DN32 to DN100

PALANCAS / LEVERS



DN ND	E	H
32-100	205	57
125-200	330	70



VÁLVULAS DE MARIPOSA / BUTTERFLY VALVES

VÁLVULA DE MARIPOSA WAFER TOTAL INOX CON ASIENTO EPDM. PN16 PALANCA
WAFER TYPE BUTTERFLY VALVE FULL S.STEEL WITH EPDM SEAT. PN16 LEVER



TECFLW®
TF-BFV-W-SS

DN250-DN300



MATERIALES / CONSTRUCTION :

No.	Pieza Part	Material Material
1	Cuerpo Body	ASTM A351 CF8M
2	Disco Disc	ASTM A351 CF8M
3	Asiento Seat	EPDM
4	Eje Shaft	A.Inox AISI316 SS 316
5	Junta O-Ring	NBR
6	Circlips Circlips	A.Inox AISI316 SS 316
7	Anillo Ring	A.Inox AISI316 SS 316
8	Muelle Spring	A.Inox AISI316 SS 316

DIMENSIONES / DIMENSIONS :

DN ND	A	B	ØDe	E	ØF	H4	C	ØK	ISO	NxØZ	Par Nm Torque	Peso Weight
250	461	248	328	68	23	24	19	102	F10	4 x 11	360	24,7
300	524	280	381	78	27	24	22	102	F10	4 x 11	475	33

Par en Nm CON coeficiente de seguridad del 30% para 16 Bar.

Torque Values in Nm WITH 30% safety coefficient at 16 Bar.

PALANCAS / LEVERS

